


Solenoid valve VMPA14-M1H-MS-C-PI

Part number: 8186954

FESTO



 General operating condition

Data sheet

| Feature | Value |
|---|--|
| Valve function | 5/2-way, single solenoid |
| Type of actuation | Electrical |
| Valve size | 14 mm |
| Standard nominal flow rate (standardised to DIN 1343) | 550 l/min ... 670 l/min |
| Operating voltage | 24 V DC |
| Operating pressure | -0.09 MPa ... 0.8 MPa |
| Operating pressure | -0.9 bar ... 8 bar |
| Design | Piston gate valve |
| Type of reset | Mechanical spring |
| Approval | c UL us - Recognised (Oil) |
| Degree of protection | IP65 In mounted state To IEC 60529 |
| Sealing principle | Soft |
| Mounting position | Any |
| Manual override | Detenting Non-detenting |
| Type of piloting | Piloted |
| Flow direction | Reversible |
| Symbol | 00997391 |
| Switching element function | N/C contact |
| lap | Overlap |
| Switching position indicator | Via built-in sensor |
| Signal status display | Yes |
| Pilot pressure | 0.3 MPa ... 0.8 MPa |
| Pilot pressure | 3 bar ... 8 bar |
| Suitability for vacuum | Yes |
| Note on standard nominal flow rate | MPA-L: 670 l/min MPA-S: 550 l/min |
| Standard nominal flow rate with QS-8 | 550 l/min ... 670 l/min |
| Max. switching frequency | 2 Hz |
| Switching time off | 41 ms |
| Switching time on | 13 ms |
| Max. positive test pulse with 0 signal | 400 µs |
| Max. negative test pulse with 1 signal | 200 µs |
| Switching output | PNP |
| Permissible voltage fluctuations | +/-25% |

| Feature | Value |
|---|--|
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Vibration resistance | Transport application test with severity level 2 to FN 942017-4 and EN 60068-2-6 |
| Shock resistance | Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27 |
| Corrosion resistance class CRC | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Storage temperature | -20 °C ... 40 °C |
| Media temperature | -5 °C ... 50 °C |
| Relative air humidity | Max. 90% at 40 °C |
| Ambient temperature | -5 °C ... 50 °C |
| Max. tightening torque for valve mounting | 0.65 Nm |
| Product weight | 118 g |
| Operating voltage range, DC sensor | 10 V ... 30 V |
| Short-circuit strength sensor | Pulsed |
| Idle current sensor | ≤10 mA |
| Max. output current sensor | 200 mA |
| Max. switching frequency sensor | 5000 Hz |
| Residual ripple sensor | ±10% |
| Voltage drop sensor | ≤2 V |
| Sensor connection | Plug 3-pin M8x1 |
| Type of mounting | With through-hole |
| Note on materials | RoHS compliant |
| Material seals | NBR |
| Material housing | Die-cast aluminium |