

# Service unit combination MSB4-1/4:I1:I3

Part number: 8233006

FESTO



 General operating condition

## Data sheet

Feature	Value
Size	4
Series	MS
Mounting position	Vertical +/-5°
Condensate drain	Manual, rotating
Design	Fibre filter
Max. condensate volume	19 ml
Bowl guard	Plastic bowl guard
Symbol	00991740
Operating pressure	0 MPa ... 1.4 MPa
Operating pressure	0 bar ... 14 bar
Operating pressure	0 psi ... 203 psi
Max. standard flow rate	360 l/min
Operating medium	Compressed air to ISO 8573-1:2010 [6:-:4] Inert gas
Corrosion resistance class CRC	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Storage temperature	-10 °C ... 60 °C
Air purity class at output	Compressed air to ISO 8573-1:2010:[5:-:3]
Media temperature	-10 °C ... 60 °C
Ambient temperature	-10 °C ... 60 °C
Product weight	400 g
Type of mounting	With accessories
Pneumatic connection, port 1	G1/4
Pneumatic connection, port 2	G1/4
Material seals	NBR
Material filter	Borosilicate fibre
Material housing	Die-cast aluminium
Material bowl	Makrolon®