

# Quick exhaust valve SE-1/2-B

Part number: 9688

FESTO



 General operating condition

## Data sheet

| Feature   | Value  |
|---|--|
| Valve function  | Quick exhaust  |
| Pneumatic connection, port 1  | G1/2   |
| Pneumatic connection, port 2  | G1/2   |
| Type of mounting  | Screw-in   |
| Standard nominal flow rate, exhaust 0.6-0.5 MPa (6-5 bar, 87-72.5 psi)  | 6480 l/min   |
| Standard nominal flow rate, air flow 0.6-0.5 MPa (6-5 bar, 87-72.5 psi) | 4560 l/min   |
| Operating pressure  | 0.3 bar ... 10 bar   |
| Ambient temperature   | -20 °C ... 75 °C   |
| Material housing  | Die-cast aluminium   |
| Operating medium  | Compressed air to ISO 8573-1:2010 [7:--]   |
| Nominal size  | 15 mm  |
| Mounting position   | Any  |
| Symbol  | 00991459   |
| Note on operating and pilot medium                                      | Lubricated operation possible (in which case lubricated operation will always be required) |
| LABS (PWIS) conformity  | VDMA24364-B1/B2-L  |
| Media temperature   | -20 °C ... 75 °C   |
| Product weight  | 200 g  |
| Pneumatic connection, port 3  | G1/2   |
| Material seals  | NBR  |