Back to overview

MEAN WELL

Search item number

Ac J. t

e: ال La**EN** English

+ Hover and scroll to zoom | Click to enlarge

MDD06G-05

DC-DC medical Converter PCB mount; Ultra-wide Input 18-75Vdc; Dual Output +-5Vdc at +-0.6A; DIP Through hole package; 2xMOPP

0 reviews Write feedback

Print preview

Availability

Stock available on request

Multiple order quantity: 15

Minimum order quantity: 1

To my wish list

To my quote list

+ Compare

No pricing available? Please request a quote today.

Specifications

Reviews (0)

Certification

Specifications

Technical data		Information		U
Brand	MEAN WELL	Commodity	8504409590	
Item number	MDD06G-05	Warranty pack	36 Months Bring-In	
Series	MDD06	RoHS	Compliant	
Description	DC-DC medical Converter PCB mount; Ultra-wide Input 18-75Vdc; Dual Output +-5Vdc at +-0.6A; DIP Through hole package; 2xMOPP	Packing quantity	15	
Application	Medical EN/UL 60601	Net weight (gram)	17	
Technology	DC/DC			
Power Format	PCB Mount - Through Hole			
Output Power (W)	6			
Output Voltage (V)	-5 5			
Output Current (A)	-0.6 0.6			
Input Voltage (V)	18 - 75			
IP Rating	No IP assigned			
Width (mm)	20.3			
Height (mm)	12.2			
Depth (mm)	31.8			
Dimming Technology	No Dimming			

Reviews (0)

There are no reviews yet.

Write feedback

Certification

All available certificates from MEAN WELL



Last viewed products

Show last viewed products

Clear



MDD06F-12

DC-DC medical Converter PCB mount; Ultra-wide Input 9-36Vdc; Dual Output +-12Vdc at +-0.25A; DIP Through hole package; 2xMOPP

No pricing available? Please request a quote today.

To my wish list

To my quote list

+ Compare





DC-DC medical Converter PCB mount; Ultra-wide Input 9-36Vdc; Dual Output +-5Vdc at +-0.6A; DIP Through hole package; 2xMOPP

No pricing available? Please request a quote today.

To my wish list

To my quote list

+ Compare

M-C09:

Heatsink for MHB75 / 100 / 150 series DC-DC converters; Horizontal fins

No pricing available? Please request a quote today.

To my wish list

To my quote list

+ Compare



AC-DC Single output enclosed power supply; Universal AC input; Output 5Vdc at 14A; Up to 5G vibration; 1U low profile

U

Add to my baske

To my wish list

To my quote list

+ Compare



Quicklinks

HomeLoginFAQWishlistMy accountBasketPower SuppliesIndustries & MarketsTechnical NotesNew ProductsProduct updatesAbout MEAN WELLCustomer ServiceInformation Request

Contact us

Addresses

Office in the Netherlands Minervum 7139 4817 ZN BREDA

+31 76 578 20 00 info@telerex-europe.com Office in Belgium Uilenbaan 90 2160 WOMMELGEM

+32 3 326 40 00 info@telerex-europe.com

Copyright © 2013-2025 MEAN WELL Web. All rights reserved. Member of the Eight Lakes group.

About MEAN WELL Web Contact us Privacy policy Terms & conditions Disclaimer

Έ