





OS160GD04N2

Print to PDF

Buy now

General Information

Extended Product Type:

OS160GD04N2

Product ID:

1SCA115881R1001

EAN:

6417019481494

Catalog Description:

OS160GD04N2 SWITCH FUSE

Long Description:

Switch-disconnector fuse, 160A, 4-pole, DIN,000/00, front operated, switched non-fusible fourth pole.

Add to Cart

Read More

Data Sheet

Downloads

Buy now

Categories

Go To Section:[ABB EcoSolutions](#)[Material Compliance](#)[Popular Downloads](#)[Environmental](#)[Ordering](#)[Dimensions](#)[Container Information](#)[Technical](#)[Technical UL/CSA](#)[Certificates and Declarations](#)[External Classifications and Standards](#)**ABB EcoSolutions****ABB Site Meeting Group Waste To Landfill Target:**[UL 2799 Zero Waste To Landfill Validation available](#)**End Of Life Disassembling Instructions:**[Switch Fuses OS100-160G Disassembly Instructions](#)**Environmental Product Declaration - EPD:**[PEP, EPD, OS100-160G](#)**Material Compliance****Conflict Minerals Reporting Template (CMRT):**[CMRT - Conflict Minerals Reporting Template](#)**REACH Declaration:**[Reach Declaration / AC Switches and Fusegear](#)**RoHS Information:**[RoHS Declaration / AC Switches and Fusegear](#)**RoHS Status:**[Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019](#)**Toxic Substances Control Act - TSCA:**[Toxic Substances Control Act \(TSCA\) Declaration / AC Switches and Fusegear](#)**Popular Downloads****Data Sheet, Technical Information:**[Switches, Switch fuses OS and QSM, OS1GB Catalog PDF](#)**Instructions and Manuals:**[Switch fuses OS100G-160G](#)**Mechanical Drawings:**[OS160GD_F_04.igs](#)**Environmental Product Declaration - EPD:**[PEP, EPD, OS100-160G](#)**Environmental**

Pollution Degree:

3

Ordering**Minimum Order Quantity:**

1 piece

Customs Tariff Number:

85365080

Country of Origin:

Finland

Dimensions**Product Net Width:**

182 mm

Product Net Height:

140 mm

Product Net Depth / Length:

130 mm

Product Net Weight:

2.4 kg

5.29 lb

Container Information**Package Level 1 Units:**

box 1 piece

Package Level 1 Width:

170 mm

6.7 in

Package Level 1 Depth / Length:

220 mm

8.7 in

Package Level 1 Height:

150 mm

5.9 in

Package Level 1 Gross Weight:

2.6 kg

5.6 lb

Package Level 1 EAN:

6417019481494

Technical**Conventional Free-air Thermal Current (I_{th}):** $\Theta = 40\text{ }^{\circ}\text{C}$ 160 A**Conventional Thermal Current (I_{the}):**

Fully Enclosed 160 A

Fourth Pole Position:

Right Side

Fourth Pole Type:

Switched - With Solid Link

Fuse Size:

NH000

NH00

Fuse System:

DIN

Handle Type:

Handle and shaft not included

Mounting Type:

Base mounting

Number of Poles:

4P

Operating Mode:

Front Operated

Pollution Degree:

3

Position of Line Terminals:

Top In - Bottom Out, Bottom In - Top Out

Power Loss:

at Rated Current 8 W

Rated Conditional Short-Circuit Current (I_{nc}):

(690 V) 80 kA

Rated Current (I_n):

Main Circuit 160 A

Rated Impulse Withstand Voltage (U_{imp}):

8 kV

Rated Insulation Voltage (U_i):

1000 V

Rated Operational Current AC-21A (I_e):

(500 V) 160 A

(690 V) 160 A

Rated Operational Current AC-22A (I_e):

(500 V) 160 A

(690 V) 160 A

Rated Operational Current AC-23A (I_e):

(500 V) 160 A

(690 V) 160 A

Rated Operational Power AC-23A (P_e):

(220 ... 240 V) 45 kW

(400 V) 75 kW

(415 V) 75 kW

(500 V) 90 kW

(690 V) 132 kW

Rated Operational Voltage:

Main Circuit 690 V AC

Rated Short-time Withstand Current Low Voltage (I_{cw}):

for 1 s 5 kiloampere rms

Standards:

IEC 60947-3

Switches Operating Mechanism:

04 (Left Side)

Terminal Type:

Lug terminals

Terminal Width:

20 mm

Tightening Torque:

15 ... 22 N·m

Technical UL/CSA**Tightening Torque:**

15 ... 22 N·m

Certificates and Declarations**A2L Certificate – IEC:**

[A2L Refrigerant Declaration of Conformity / OS100-800](#)

ATEX Certificate:

[No certification needed](#)

CCC Certificate:

[CCC OS100-160G_2015.pdf](#)

Declaration of Conformity - CE:

[Declaration of Conformity / OS100G_ OS125G_ OS160G](#)

DNV GL Certificate:

[DNV GL Certificate / OS20...160](#)

UL Certificate:

[No certification needed](#)

External Classifications and Standards**Object Classification Code:**

Q

ETIM 8:

EC001040 - Fuse switch disconnecter

ETIM 9:

EC001040 - Fuse switch disconnecter

UNSPSC:

39122233

IDEA Granular Category Code (IGCC):

5291 >> Fuse switch disconnecter

eClass:

V11.1 : 27371401

WEEE Category:

5. Small Equipment (No External Dimension More Than 50 cm)

E-Number (Finland):

3660219



PRODUCTS

- Offerings A-Z
- Services
- Where to buy

INDUSTRY SOLUTIONS

- Channel partners
- Buildings and infrastructure
- Industrial automation
- Marine
- Oil & gas
- Power generation

INVESTORS

- Investor & shareholder resources
- Quarterly results & annual reports
- Corporate governance
- Calendar, events and publications

COMPANY

- Customer events
- News & media
- Who we are
- Innovation
- Careers
- Sustainability
- Our values
- Supplying



Provider
information

Privacy Notice

Cookie settings

© 1995 - 2025