Search item number

Ac Just

La**EN**uage: English

Back to overview

геедраск

+ Hover and scroll to zoom | Click to enlarge

SPBW03G-05

DC-DC Converter PCB mount; Input 18-75Vdc; Single Output 5Vdc at 0.6A; SIP Through hole package

0 reviews Write feedback

Print preview

Availability

Stock available on request

Multiple order quantity: 2100

Minimum order quantity: 1

To my wish list

To my quote list

+ Compare

No pricing available? Please request a quote today.

Specifications Reviews (0) Datasheet Certification Downloads

Specifications

Technical data		Information	
Brand	MEAN WELL	Commodity	8504409590
Item number	SPBW03G-05	Warranty pack	36 Months Bring-In
Series	SPBW03	RoHS	Compliant
Description	DC-DC Converter PCB mount; Input 18-75Vdc; Single Output 5Vdc at 0.6A; SIP Through hole package	Packing quantity	2100
Technology	DC/DC	Net weight (gram)	4.8
Power Format	PCB Mount - Through Hole		
Output Power (W)	3		
Output Voltage (V)	5		
Output Current (A)	0.6		
Input Voltage (V)	18 - 75		
IP Rating	No IP assigned		
Width (mm)	9.2		
Height (mm)	11.1		
Depth (mm)	21.8		
Dimming Technology	No Dimming		

Reviews (0)

There are no reviews yet.

Write feedback

Datasheet

Datasheets & test reports provided by MEAN WELL



🚠 Datasheet



Certification

All available certificates from MEAN WELL



E Declaration

Downloads

Drawing



Short Form | DC-DC Converter

Last viewed products

Show last viewed products

Clear



SPBW03G-03

DC-DC Converter PCB mount; Input 18-75Vdc; Single Output 3.3Vdc at 0.7A; SIP Through hole package

No pricing available? Please request a quote today.

To my wish list

To my quote list

+ Compare



DC-DC Converter PCB mount; Input 9-36Vdc; Single Output 15Vdc at 0.2A; SIP Through hole package



To my wish list

To my quote list

+ Compare SPBW03F-12



DC-DC Converter PCB mount; Input 9-36Vdc; Single Output 12Vdc at 0.25A; SIP Through hole package

No pricing available? Please request a quote today.

To my wish list


To my quote list

+ Compare



AC-DC Triple output enclosed power supply; Output +5Vdc at 12A +12Vdc at 5A -12Vdc at 1A

U



EIGHT GROUP

Quicklinks

HomeLoginFAQWishlistMy accountBasketPower SuppliesIndustries & MarketsTechnical NotesNew ProductsProduct updatesAbout MEAN WELLCustomer ServiceInformation Request

Contact us

Addresses

Office in the Netherlands Minervum 7139 4817 ZN BREDA Office in Belgium Uilenbaan 90 2160 WOMMELGEM

+31 76 578 20 00 +32 3 326 40 00 info@telerex-europe.com info@telerex-europe.com

Copyright © 2013-2025 MEAN WELL Web. All rights reserved. Member of the Eight Lakes group.

About MEAN WELL Web Contact us Privacy policy Terms & conditions Disclaimer

Έ